

**Store Name:** \_\_\_\_\_ **Store Number:** \_\_\_\_\_

**Height** (if all same): \_\_\_\_\_

*Note: measure height from header to floor or counter*

If there are any height changes, please provide below.

Height: \_\_\_\_\_ for distance: \_\_\_\_\_ for reference point: \_\_\_\_\_

Height: \_\_\_\_\_ for distance: \_\_\_\_\_ for reference point: \_\_\_\_\_

Height: \_\_\_\_\_ for distance: \_\_\_\_\_ for reference point: \_\_\_\_\_

Sketch of layout (looking from top down):

*Inside (secured site)*

L
R

*Outside*

**Pocket Details:**

Minimum Width: 10"  
Depth Required: Roughly 2" per linear foot of curtain.

**Lock Heights:**

If over counter: Lock cylinder height is 21.5" from top of counter.  
If all over floor: Lock cylinder height is 41.5" from floor.

**Lock Options:**

Double Lock: Typically used in posts at a free end of a grille for greater security. Has shootbolts to both the floor and track.  
Single Lock: Used in Mid Posts. Has a shootbolt to the floor only.

**Track:**

Radius Options: 14" Radius at 45° or 90° - 24" Radius at 45° or 90°

**General Notes:**

- Design and installation of the support header is by others.
- Header and related structure must support 180PLF with max deflection < 1"
- An 8" minimum clear path is required.
- Provide any information necessary to layout the track in the layout sketch.

**Special Notes:** \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_